

Golden Fox Sign LLC 3327 B Street Philadelphia, PA 19124 (610) 483-9041 (856) 725-7147 goldenfoxsign@gmail.com

Date: 1/3/2025

Client: European Republic

Address: 213 Chestnut Street

City, State: Philadelphia, PA

Contact: Farid Alinoor

Phone: 267-368-9011

E-mail: falinoor@gmail.com

Job Site: European Republic

Address: 213 Chestnut Street

City, State: Philadelphia, PA

Account Exec: Mahir Atak

Designer: Eyad Saleh

Approved By: Mahir Atak

Client:

X

**LICENSE NO. 802014** 

**FULLY LICENSED & INSURED** 

## Sign Rendering for 213 Chestnut Street



FASTENER			HORIZONTAL SPACING PER WALL CONSTRUCTION (INCHES)				
HARDWARE	DIA.	QTY. PER SPACING	MASONRY	WOOD	EIFS/DRYVIT OVER 1/2" MIN PLYWOOD	EIFS/DRYVIT OVER 1/2" MIN GYPSUM/DENGLASS	METAL PANEL OVER
WOOD SCREW <sup>1,7</sup>	#10	2	NO	24	24	24	NO
TEK SCREW <sup>2</sup>	#10	2	NO	NO	NO	NO	24
LAG BOLT <sup>3</sup>	3/8"	2	NO	36	24	24	NO
THRU-BOLT <sup>4</sup>	3/8"	2	48	NO	24	24	24
EXPANSION ANCHOR <sup>5</sup>	3/8"	2	48	NO	NO	NO	NO
CARBON STEEL SCREW ANCHOR	3/8"	2	48	NO	NO	NO	NO
TOGGLE BOLT <sup>8</sup>	3/8"	2	24	NO	18	18	24

MINIMUM 1.5" EMBEDMENT INTO WOOD STUDS, OR MIN 1/4" PROTUDED FROM THE BACK OF PLYWOOD.

MIN 1/4" PROTUDED FROM THE BACK OF METAL STUD

IINIMUM 2.5" EMBEDMENT INTO WOOD STUDS, OR MIN 1/4" PROTUDED FROM THE BACK OF PLYWOOD

3) ANCHORS REQUIRE A MINIMUM 2" EMBEDMENT, ANCHOR SHALL BE INSTALLED IN CONCRETE OR GROUT FILLED CMU UNITS ONLY.

4) REQUIRES 2"x2"x1/4" STEEL BACKING PLATE.

USE HILTI HLC SLEEVE ANCHOR OR EQUIVALENT WITH 1-1/4" MIN EMBEDMENT

USE HILTI KWIK HUS-E OR APPROVED EQUIVALENT WITH 1-5/8" MIN EMBEDME

MINIMUM 20 GAUGE METAL THICKNESS

THROUGH BLOCK FACE FOR CLAY BRICKS

 IF THE CONTRACTOR ENCOUNTERS A METAL/WOODEN STUD, HE/SHE SHALL FOLLOW THE LAG/TEK SCREW GUIDELINE AS SHOWN ON THE SCHEDULE ABOVE THE CONTRACTOR SHALL MAKE EVERY ATTEMPT TO USE STUDS WHENEVER POSSIBLE.

NOTE: THIS FASTENER SCHEDULE IS INTENDED FOR USE WITH SIGN CONNECTION TO BUILDING ONLY. IT IS ASSUMED THAT THE BUILDING IS RIGID, FREE OF STRUCTURAL DEFECTS, AND STRUCTURALLY SUFFICIENT TO CARRY THE LOAD OF THE SIGN. CONTRACTOR SHALL FOLLOW FASTENER SCHEDULE TO DETERMINE FASTENER TYPE TO BE USED FOR INSTALLATION AND SHALL ENSURE THE FASTENER HAS A RIGID AND STRONG CONNECTION. CONTRACTOR SHALL FOLLOW MANUFACTURERS SPECS FOR FASTENER/ANCHOR INSTALLATION. CONTRACTOR SHALL ENSURE THAT FASTENER BEARS ON WALL FACADE IMMEDIATELY AFTER INSTALLATION. CONTRACTOR SHALL NOT USE EXISTING HOLES PRESENT IN THE CURRENT FASCIA FOR FASTNER INSTALLATION.



165"

## **NOTES**

Golden Fox Sign LLC is manufacturing and installing an aluminum dibond sign with graphics only on existing platform. No other modifications will be done.

SIGN RENDERING





